

Product Name: MAGNUM R.T.U. Product identifier: 48P Revision Date: 07-18-2015

# Parker Distributing Co., Inc.

## 1. Identification

Product Name: Product identifier: Relevant identified uses of the substance or mixture and uses advised against:	MAGNUM RTU 48P Mag Wheel Cleaner
Chemical Manufacturer: Distributor:	Parker Distributing Company 4701 West F. M. Road 3331 Canyon, Texas 79015
Emergency telephone number:	INFOTRAC 1-800-535-5053

### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200; GHS Hazard Symbols:



GHS Classification:	Skin Corrosion/Irritation Category 2	
	Serious Eye Damage/Eye Irritation Category 2A	
	Flammable Liquid Category 4	
GHS Signal Word:	Warning	
GHS Hazard Statements:	Cumbustible Liquid	
	Causes skin irritation.	
	Causes serious eye irritation.	
GHS Precautionary Statements:		
Safety Precautions:	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.	
	Wash thoroughly after handling.	
	Wear protective gloves/protective clothing/eye protection/face protection.	
First Aid Measures:	IF ON SKIN: Wash with plenty of soap and water.	
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,	
	if present and easy to do. Continue rinsing.	
	Specific treatment (see on this label).	



Product Name: MAGNUM R.T.U. Product identifier: 48P Revision Date: 07-18-2015

	If skin irritation occurs: Get medical advice/attention.
	If eye irritation persists: Get medical advice/attention.
	Take off contaminated clothing and wash before reuse.
	In case of fire: Use for extinction.
Storage:	Store in a well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container in accordance with
	local/regional/national/international regulation for hazardous wastes.
Hazards not otherwise classified:	MEDICAL CONDITIONS AGGRAVATED: dermatitis may be aggravated by excessive exposure to skin.

3. Composition/information on ingredients		
Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Triethanolamine	102-71-6	1-5
Caustic Soda	1310-73-2	1-2
Sodium Metasilicate	7757-82-6	0-4
Phosphate dodecaydrate	10101-89-0	1-2
Glycol Ether	111-76-2	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. First-aid measures

**Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. This corrosive material can cause immediate and permanent eye damage. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eye with water for 20 minutes. Get medical attention. Seek immediate medical attention.

Skin Contact:	Wash with soap and water under a drench shower. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately. Wash affected area thoroughly with soap and water.
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If inhaled, remove victim from exposure to a well-ventilated area.
Ingestion:	Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately and give the medical care provider with this MSDS. Do not induce vomiting unless directed to do so by medical personnel. Drink 1-2



Product Name: MAGNUM R.T.U. Product identifier: 48P Revision Date: 07-18-2015

	glasses of milk to dilute product. Call a physician or poison control center immediately. Never give anything by mouth to an
	unconscious person
Immediate medical attention	No additional first aid information available
and special treatment needed,:	
5. Fire-fighting measures	
Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water
Suitable extinguishing media.	spray when fighting fires. Water or foam may cause frothing if
	liquid is burning but it still may be a useful extinguishing agent if
	carefully applied to the fire. Do not direct a water stream directly
	into the hot burning liquid. Water spray Alcohol foam Dry chemical
	Carbon dioxide
Unsuitable extinguishing media:	No data available
Fire and/or Explosion Hazards:	Material may be ignited if preheated to temperatures above the
	flash point in the presence of a source of ignition. Material will not
	burn.
Hazardous Combustion	Carbon monoxide, Carbon dioxide
Products:	
Special protective equipment	Do not enter fire area without proper protection including self-
and precautions for fire-	contained breathing apparatus and full protective equipment. Fight
fighters:	fire from a safe distance and a protected location due to the
	potential of hazardous vapors and decomposition products.
6. Accidental release measures	
or Accounter release measures	

Personal precautions, protective equipment and emergency procedures:	Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.
Methods and material for containment and cleaning up:	No special spill clean-up considerations. Collect and discard in regular trash. SMALL SPILL: Contain and collect with absorbent. LARGE SPILLS: Shut off leak if safe to do so. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Prevent spilled material from contaminating soil, entering sanitary sewers, storm sewers, and drainage systems, and entering bodies of water or ditches that lead to waterways.



Product Name: MAGNUM R.T.U. Product identifier: 48P Revision Date: 07-18-2015

7. Handling and storage	
Precautions for safe handling:	Toxic or severely irritating material. Avoid contacting and avoid
	breathing the material. Use only in a well ventilated area. Keep out of the reach of children.
Conditions for safe storage:	Store in a cool dry place. Isolate from incompatible materials. Keep
conditions for sale storage.	from freezing, STORAGE TEMPERATURE: 32°F Minimum to 110°F Maximum. Shelf life is one year.
Materials to Avoid/Chemical Incompatibility::	Strong oxidizing agents Acids Metals Water Organic halides Strong acids

## 8. Exposure controls/personal protection

## <u>Limits:</u>

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Caustic Soda	2 mg/m3	2 mg/m3	
Appropriate engineering controls.:	Local exhaust ventilation, process enclosures, or other engineering controls are necessary when handling or using this product to avoid overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits.		
Eye Protection:	Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available. Safety Glasses or goggles with splash guards or side shields.		
Skin Protection:	Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Use Nitrile/ Vinyl gloves		
Respiratory Protection:	Respiratory protection must be used when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. A supplied air type respirator may be required. NIOSH respirator - (organic vapor) in absence of proper environmental control.		
Other Protective Equipment:			
General Hygiene Conditions:	Keep out of the reach of cl	nildren.	

Product Name: MAGNUM R.T.U. Product identifier: 48P Revision Date: 07-18-2015 Replaces:

#### 9. Physical and chemical properties

Appearance (physical state):	Liquid
Color:	Green
Odor:	Glycol ether
Odor threshold:	No data available
pH:	> 12
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	100
Flash Point (°C):	63
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper Flammable/Explosive Limit:	No data available
Lower Flammable/Explosive Limit:	No data available
Vapor Pressure:	17.5 MMHG@20C/68F
Vapor Density:	No data available
Relative Density:	1.1
Solubility(ies):	Complete; 100%
Partition coefficient: n-octanol/water:	No data available
Auto-ignition Temperature (°C):	No data available
Decomposition Temperature::	No data available
Viscosity:	No data available

### 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Conditions to avoid:	None known. Contamination Contact with water.
Incompatible materials:	Strong oxidizing agents Acids Metals Water Organic halides Strong acids
Hazardous decomposition products:	Carbon dioxide Carbon monoxide

## 11. Toxicological information

Likely routes of exposure	Skin contact, Eye contact, Ingestion
(inhalation, ingestion, skin and	
eye contact):	

### Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can be corrosive to the respiratory tract causing severe irritation and tissue damage	
	Irritating to the nose, throat, and respiratory tract.	
Skin Contact:	Corrosive to skin tissue. Can cause chemical burns. Corrosive, causes skin burns and	
	permanent skin damage (scarring). May cause skin irritation.	

Product Name: MAGNUM R. T. U. Product identifier: 48P Revision Date: 07-18-2015 Replaces:

Skin Absorption:	No absorption hazard in normal industrial use. Causes skin burns		
Eye Contact:	Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can		
	quickly lead to permanent injury including blindness. Causes eye burns.		
Ingestion Irritation:	Corrosive to tissue. Can cause severe and permanent damage to mouth, throat,		
	stomach. Aspiration may lead to lung damage. Can burn mouth, throat, and		
	stomach.		
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.		
Long-Term (Chronic) Health Ef	fects:		
Carcinogenicity:	None of the substances have been shown to cause cancer in long termanimal		
	studies. Not a carcinogen according to NTP, IARC, or OSHA. Cancer hazard! Contain		
	a material that can cause cancer.		
Reproductive and	No data available to indicate product or any components present at greater than		
Developmental Toxicity:	0.1% may cause birth defects.		
Mutagenicity:	No data available to indicate product or any components present at greater than		
	0.1% is mutagenic or genotoxic.		
Inhalation:	Upon prolonged and/or repeated exposure, can be corrosive to the respiratory trac		
	causing severe irritation and tissue damage. Upon prolonged and/or repeated		
	exposure, can be corrosive to the respiratory tract causing severe irritation and		
	tissue damage.		
Skin Contact:	Upon prolonged or repeated contact, corrosive to skin tissue. Cancause chemical		
	burns.		
Skin Absorption:	Upon prolonged or repeated exposure, no hazard in normal industrial use.		

#### **Component Toxicology Data**

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
No data available			

### Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available			

### 12. Ecological information

Ecotoxicity (aquatic and	Harmful to aquatic life.
terrestrial, where available):	
Persistence and degradability:	No data available
Mobility in soil:	No data available
Other adverse effects (such as	No data available
hazardous to the ozone layer):	

Product Name: MAGNUM R. T. U. Product identifier: 48P Revision Date: 07-18-2015 Replaces:

<b>Ecological Toxicity Data</b>			
Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations	
Description of waste residues:	Spent or discarded material may be a hazardous waste.
Safe Handling of Waste:	Disposal must be in accordance with applicable Federal,
	State/Provincial and Local regulations.
Waste treatment methods	Dispose of by incineration following Federal, State, Local, or
(including packaging):	Provincial regulations.
14. Transport information	
UN proper shipping name:	Refer to bill of lading or container label for DOT or other transportation hazard classification, if any.

15. Regulatory information	
TSCA Status:	All chemicals in this product are listed, or are exempt from
	listing on the TSCA Inventory.

#### Regulated Components:

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Caustic Soda	1310-73-2	Ν	Ν	Y	Ν

16. Other information, including date of preparation or last revision.			
Revision Date:	07-18-2015		
<b>Revision Number:</b>	5		

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances